

ENMAR ULTRA PLUS 80W-90

PRODUCT DESCRIPTION

ENMAR ULTRA PLUS 80W-90 is a mineral universal gear oil for use in manual transmissions and axle gearboxes in both passenger cars and commercial vehicles suitable for API GL-5 applications.

APPLICATIONS

ENMAR ULTRA PLUS 80W-90 is miscible and compatible with conventional branded gear oils. However, mixing with other gear oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when converting to ENMAR ULTRA PLUS 80W-90. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Always follow equipment manufacturer's recommendation for required lubricant performance levels and oil change intervals.

BENEFITS

ENMAR ULTRA PLUS 80W-90 provides:

- ◆ Superior load carrying ability.
- ◆ Reduced gear wear.
- ◆ Minimal spalling or welding.
- ◆ Excellent oxidation stability.
- ◆ Protection against rust and corrosion.

Technical Data *		
ENMAR ULTRA PLUS 80W-90		
Density at 15 °C DIN 51757,	g/ml	0.895
Colour DIN ISO 2049,	ASTM	1.5
Flash Point, CoC DIN ISO 2592,	°C	220
Pour Point DIN ISO 3016,	°C	-27
Neutralization Number FLV-N7 / DIN 51558,	mgKOH/g	1
Dynamic Viscosity at – 26°C DIN 51398,	mPas	62,000
Kinematic Viscosity at 40°C DIN 51562-1,	mm ² /s	134
Kinematic Viscosity at 100°C DIN 51562-1,	mm ² /s	14.4
Viscosity Index DIN ISO 2909		106

* The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible.

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENMAR Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.